High level Petri nets Extending classical Petri nets with color, time and hierarchy (informal introduction)

prof.dr.ir. Wil van der Aalst

Technische Universiteit **Eindhoven** University of Technology

1.336 1. 1


Where innovation starts

TU

Limitations of classical Petri nets


- Inability to test for zero tokens in a place.
- Models tend to become large.
- Models cannot reflect temporal aspects
- No support for structuring large models, cf. topdown and bottom-up design

Inability to test for zero tokens in a place




"Tricks" only work if p is bounded

Models tend to become (too) large




Models tend to become (too) large (2)




Size linear in the number of tracks.

Models cannot reflect temporal aspects



HLPN-5

No support for structuring large models



HLPN-6

High-level Petri nets

- To tackle the problems identified.
- Petri nets extended with:
 - Color (i.e., data)
 - Time
 - Hierarchy
- For the time being be do not choose a concrete language but focus on the main concepts.
- Later we focus on a concrete language: CPN.
- These concepts are supported by many variants of CPN including ExSpect, CPN AMI, etc.

Example: CPN Tools

CONTRACTOR STREET, NO. 1


Technische Universiteit **Eindhoven** University of Technology

Where innovation starts


P

TU


Classical net



Extension with color



Extension with time



_ 8 ×

